

## PY26-27 Wisconsin Weatherization Field Guide Summary of Changes

Section	Revision
<b>Section 1.4.1 (2)</b>	Updated language for material specifications when damming around chimneys, flues and B-vents.
<b>Section 2.2.1 (2)</b>	Added requirement to keep a 3-inch clearance for all active chimneys, flues or B-vents.
<b>Section 2.2.1.1</b>	Added verbiage for Enclosed Attic Pre-Insulation Prep.
<b>Section 3.3 (2)</b>	Added language when testing 2-stage forced air heating systems.
<b>Section 3.5.1</b>	Removed reference to installing an outside temperature sensor on a north facing exterior wall.
<b>Section 5.4.5</b>	Added language when installing gutters and downspouts.
<b>Section 5.11.1</b>	Added language to install temperature and pressure relief valve discharge pipe.
<b>Section 5.12.3</b>	Add verbiage for minimum CFM for exhaust fans in bathrooms and kitchens.
<b>Section 5.12.3 (5)</b>	Updated language minimum R-value to insulate exhaust fan housing in non-conditioned spaces.
<b>Section 5.12.4 (9)</b>	Updated language minimum R-value to insulate exhaust fan housing in non-conditioned spaces.
<b>Sections – All</b>	Updated the FG along with photos and images for ADA compliance.